





# Sentinel® Connector Systems Inc.

1953 Stanton Street

York, Pa. 17404

PART NO.: 111-08080091L34

- \* EIGHT CONDUCTOR MODULAR PLUG
- \* FOR CONDUCTORS WITH AN O.D. RANGE OF .048 -.052
- \* USES .012 CONTACT
- \* PRODUCT REQUIRES CONDUCTIVE LOAD BAR
- \* FOR CAT 6 PATCH CORD APPLICATIONS
- \* FOR SOLID OR STRANDED WIRE APPLICATIONS



"PATENTED"

**PERFORMANCE:**

SPECIFICATIONS :  
 MEETS OR EXCEEDS CATEGORY 6 ANSI/EIA 568-C.2  
 PERFORMANCE TUNED TO CABLES MEETING CATEGORY 6 SPECIFICATIONS.

**CONTACT MATERIAL:**

PHOSPHOR BRONZE - .012 THK

**CONTACT PLATING:**

50 MICRO-INCH : OTHER PLATING OPTIONS AVAILABLE  
 SELECTIVE 24 CARAT HARD GOLD PLATE IN CONTACT AREA  
 OVER 100 MICRO-INCH MINIMUM NICKEL PLATE  
 PER CURRENT SELECTIVE GOLD PLATING REQUIREMENTS.

**PLUG MATERIAL:**

POLYCARBONATE

**PLUG TOLERANCES AND DIMENSIONS:**

\* COMPLIES WITH ANSI/TIA-1096-A REQUIREMENTS

**U.L. RECOGNIZED**

File# E188111

**FLAME AUTO EXTINGUISH**

94-V0

**OPERATION TEMPERATURE:**

-40°C TO +85°C

**INSERTION/EXTRACTION LIFE:**

1000 CYCLES

**CONTACT RESISTANCE:**

10 MILLOHMS MAX.

**CURRENT/VOLTAGE:**

30 VAC/42 VDC AT 1.5 AMPS

**(RoHS COMPLIANT)**

\* FORMER COMPLIANCE, FCC PART 68.500

