




Sentinel® Connector Systems Inc.

1953 Stanton Street


York, Pa. 17404

PART NO.: 111S080800F3LA4

- * EIGHT CONDUCTOR MODULAR PLUG
- * FOR HIGH SPEED APPLICATION
- * FOR CONDUCTORS WITH AN O.D. RANGE OF .031-.033
- * FOR CAT6 AND 6a PATCH CORD APPLICATIONS
- * SHIELDED VERSION MODULAR PLUG
- * USE FOR ONLY STRANDED CONDUCTORS
- * PRODUCT REQUIRES A SPECIAL LOAD BARS, LB018, LB030
- * DESIGNED TO BE USED WITH SENTINEL COMPATIBLE LOAD BARS
- * SENTINEL LOGO



SECTION VIEW WITH NO SHIELD



"PATENTED"

SPECIFICATIONS :

PERFORMANCE: MEETS OR EXCEEDS CATEGORY 6a ANSI/TIA 568.2-D PERFORMANCE TUNED TO CABLES MEETING CATEGORY 6 SPECIFICATIONS.

CONTACT MATERIAL: PHOSPHOR BRONZE - .014 THK
CONTACT PLATING: 50 MICRO-INCH : OTHER PLATING OPTIONS AVAILABLE
 SELECTIVE 24 CARAT HARD GOLD PLATE IN CONTACT AREA
 OVER 100 MICRO-INCH MINIMUM NICKEL PLATE
 PER CURRENT SELECTIVE GOLD PLATING REQUIREMENTS.

SHIELD MATERIAL: .012 THK CDA-260 1/4 HARD BRASS
SHIELD PLATING: 100% TIN, 100-150 MICRO-INCH TIN PLATED

PLUG MATERIAL: POLYCARBONATE
PLUG TOLERANCES AND DIMENSIONS: * COMPLIES WITH ANSI/TIA-1096-A REQUIREMENTS

FLAME AUTO EXTINGUISH 94-V0 - File# E188111

OPERATION TEMPERATURE: -40°C TO +85°C

INSERTION/EXTRACTION LIFE: 1000 CYCLES

CONTACT RESISTANCE: 10 MILLOHMS MAX.

CURRENT/VOLTAGE: 30 VAC/57 VDC AT 1.5 AMPS

(RoHS COMPLIANT) * FORMER COMPLIANCE, FCC PART 68.500

