

# Commercial Data Cables

## DATAMAX CATEGORY 6A

### 26 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2942 (BLACK), 2943 (BROWN), 2944 (RED), 2945 (ORANGE), 2946 (YELLOW), 2947 (GREEN), 2948 (BLUE), 2949 (VIOLET), 2950 (GRAY), 2951 (WHITE), 2952 (BEIGE), 2953 (PINK), 2991 (AQUA)	26 Stranded (7x34) .036" Insulated Conductor OD .235" Jacket OD	F/UTP With Spline	CMG, CMR	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
2978 (BLACK), 2979 (BROWN), 2980 (RED), 2981 (ORANGE), 2982 (YELLOW), 2983 (GREEN), 2984 (BLUE), 2985 (VIOLET), 2986 (GRAY), 2987 (WHITE), 2988 (BEIGE), 2989 (PINK)	26 Stranded (7x34) .036" Insulated Conductor OD .265" Jacket OD	F/UTP With Spline	CMX, LSZH	111S08080095HA4	7mm (.275" Jacket OD)	900020
2056 (BLACK), 2057 (BROWN), 2058 (RED), 2059 (ORANGE), 2060 (YELLOW), 2061 (GREEN), 2062 (BLUE), 2063 (VIOLET), 2064 (GRAY), 2065 (WHITE), 2066 (BEIGE)	26 Stranded (7x34) .039" Insulated Conductor OD .223" Jacket OD	F/UTP No Spline	CMP	111S080800C7LA4	6mm (.240" Jacket OD)	900005/900216
2279 (BLACK), 2280 (RED), 2281 (ORANGE), 2282 (YELLOW), 2283 (GREEN), 2284 (BLUE), 2285 (VIOLET), 2286 (GRAY), 2287 (WHITE)	26 Stranded (7x34) .0405" Insulated Conductor OD .235" Jacket OD	Relaxed F/UTP No Spline	CM-ST1, CM, LSZH	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216

2246 (BLACK), 2247 (BROWN), 2248 (RED), 2249 (ORANGE), 2250 (YELLOW), 2251 (GREEN), 2252 (BLUE), 2253 (VIOLET), 2254 (GRAY), 2255 (WHITE), 2256 (BEIGE), 2257 (PINK), 2258 (AQUA), 2259 (LT Blue)	26 Stranded (7x34) .0405" Insulated Conductor OD .233" Jacket OD	Relaxed F/UTP No Spline	CMG, CMR, EU CE MARK	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
---	--	-------------------------------	-------------------------	-----------------	--------------------------	---------------

## 28 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2231 (BLACK), 2232 (BROWN), 2233 (RED), 2234 (ORANGE), 2235 (YELLOW), 2236 (GREEN), 2237 (BLUE), 2238 (VIOLET), 2239 (GRAY), 2240 (WHITE), 2241 (BEIGE), 2242 (LIGHT BLUE), 2243 (PINK), 2244 (AQUA), 2245 (LIME GREEN)	28 Stranded (7x36) .0325" mim .0331" max Insulated Conductor OD .186" Jacket OD	F/UTP No Spline	CMR	111S080800F3LA4	5mm (.197" Jacket OD) MUST USE B00067L BOOT for proper termination and strain relief	900005/900216
2270 (BLACK), 2271 (RED), 2272 (ORANGE), 2273 (YELLOW), 2274 (GREEN), 2275 (BLUE), 2276 (VIOLET), 2277 (GRAY), 2278 (WHITE)	28 Stranded (7x36) .0325" mim .0331" max Insulated Conductor OD .190" Jacket OD	F/UTP No Spline	CM-ST1, CM, LSZH	111S080800F3LA4	5mm (.197" Jacket OD) MUST USE B00067L BOOT for proper termination and strain relief	900005/900216
2034 (BLACK), 2035 (BROWN), 2036 (RED), 2037 (ORANGE), 2038 (YELLOW), 2039 (GREEN), 2040 (BLUE), 2041 (VIOLET), 2042 (GRAY), 2043 (WHITE), 2044 (STARLIGHT BEIGE)	28 Stranded (7x36) .031" Insulated Conductor OD .186" Jacket OD	F/UTP No Spline	CMP	111S080800F3LA4	5mm (.197" Jacket OD) MUST USE B00067L BOOT for proper termination and strain relief	900005/900216

## DATAMAX CATEGORY 6

### 24 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2200 (BLACK), 2201 (BROWN), 2202 (RED), 2203 (ORANGE), 2204 (YELLOW), 2205 (GREEN), 2206 (BLUE), 2207 (VIOLET), 2208 (GRAY), 2209 (WHITE), 2210 (BEIGE), 2211 (LIGHT BLUE), 2212 (PINK), 2213 (AQUA), 2215 (LIME)	24 Stranded (7x32) .039" Insulated Conductor OD .220" Jacket OD	U/UTP No Shield No Spline	CMR	111-08080054L34	6mm (.240" Jacket OD)	900005/900216
2200B (BLACK), 2201B (BROWN), 2202B (RED), 2203B (ORANGE), 2204B (YELLOW), 2205B (GREEN), 2206B (BLUE), 2207B (VIOLET), 2208B (GRAY), 2209B (WHITE), 2210B (BEIGE), 2212B (PINK), 2215B (LIME)	24 Stranded (7x32) .039" Insulated Conductor OD .220" Jacket OD	U/UTP No Shield No Spline	CMG, CMR	111-08080054L34	6mm (.240" Jacket OD)	900005/900216
1300 (BLACK), 1301 (BROWN), 1302 (RED), 1303 (ORANGE), 1304 (YELLOW), 1305 (GREEN), 1306 (BLUE), 1307 (VIOLET), 1308 (GRAY), 1309 (WHITE), 1310 (BEIGE), 1312 (PINK)	24 Stranded (7x32) .039" Insulated Conductor OD .231" Jacket OD	U/UTP No Shield No Spline	CMX, LSZH	111-08080054L34	6mm (.240" Jacket OD)	900005/900216
2016 (BLACK), 2017 (RED), 2018 (ORANGE), 2019 (YELLOW), 2020 (GREEN), 2012 (BLUE), 2022 (VIOLET), 2023 (GRAY), 2024 (WHITE)	24 Stranded (7x32) .039" Insulated Conductor OD .227" Jacket OD	U/UTP No Shield No Spline	CM-ST1, CM, LSZH	111-08080054L34	6mm (.240" Jacket OD)	900005/900216

## 26 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2966 (BLACK), 2967 (BROWN), 2968 (RED), 2969 (ORANGE), 2970 (YELLOW), 2971 (GREEN), 2972 (BLUE), 2973 (VIOLET), 2974 (GRAY), 2975 (WHITE), 2976 (BEIGE), 2977 (PINK)	26 Stranded (7x34) .036" Insulated Conductor OD .265" Jacket OD	F/UTP With Spline	CMX, LSZH	111S08080095LA4	7mm (.275" Jacket OD)	900005/900216
2930 (BLACK), 2931 (BROWN), 2932 (RED), 2933 (ORANGE), 2934 (YELLOW), 2935 (GREEN), 2936 (BLUE), 2937 (VIOLET), 2938 (GRAY), 2939 (WHITE), 2940 (BEIGE), 2941 (PINK)	26 Stranded (7x34) .036" Insulated Conductor OD .235" Jacket OD	F/UTP With Spline	CM, CMG, CMR	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
2025 (BLACK), 2026 (RED), 2027 (ORANGE), 2028 (YELLOW), 2029 (GREEN), 2030 (BLUE), 2031 (VIOLET), 2032 (GRAY), 2033 (WHITE)	26 Stranded (7x34) .036" Insulated Conductor OD .235" Jacket OD	F/UTP No Spline	CM-ST1, CM, LSZH	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
2157 (BLACK), 2158 (BROWN), 2159 (RED), 2160 (ORANGE), 2161 (YELLOW), 2162 (GREEN), 2163 (BLUE), 2164 (VIOLET), 2165 (GRAY), 2166 (WHITE), 2167 (BEIGE), 2168 (PINK)	26 Stranded (7x34) .0405" Insulated Conductor OD .233" Jacket OD	Relaxed F/UTP No Spline	CMG, CMR, EU CE MARK	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216

2067 (BLACK), 2068 (BROWN), 2069 (RED), 2070 (ORANGE), 2071 (YELLOW), 2072 (GREEN), 2073 (BLUE), 2074 (VIOLET), 2075 (GRAY), 2076 (WHITE), 2077 (BEIGE)	26 Stranded (7x34) .039" Insulated Conductor OD .223" Jacket OD	F/UTP No Spline	CMP	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
--	---	--------------------	-----	-----------------	--------------------------	---------------

## 28 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2260 (BLACK), 2261 (RED), 2262 (ORANGE), 2263 (YELLOW), 2264 (GREEN), 2265 (BLUE), 2266 (VIOLET), 2267 (GRAY), 2268 (WHITE), 2269 (PINK)	28 Stranded (7x36) .0245" Insulated Conductor OD .150" Jacket OD	U/UTP No Shield No Spline	CM-ST1, CM, LSZH	111-080800B5LA4	4.06mm (.160" Jacket OD) MUST USE B00058L BOOT for proper termination and strain relief	900005/900216
2216 (BLACK), 2217 (BROWN), 2218 (RED), 2219 (ORANGE), 2220 (YELLOW), 2221 (GREEN), 2222 (BLUE), 2223 (VIOLET), 2224 (GRAY), 2225 (WHITE), 2226 (BEIGE), 2227 (LIGHT BLUE), 2228 (PINK), 2229 (AQUA), 2230 (LIME)	28 Stranded (7x36) .0245" Insulated Conductor OD .150" Jacket OD	U/UTP No Shield No Spline	CMR	111-080800B5LA4	4.06mm (.160" Jacket OD) MUST USE B00058L BOOT for proper termination and strain relief	900005/900216
2045 (BLACK), 2046 (BROWN), 2047 (RED), 2048 (ORANGE), 2049 (YELLOW), 2050 (GREEN), 2051 (BLUE), 2052 (VIOLET), 2053 (GRAY), 2054 (WHITE), 2055 (STARLIGHT BEIGE)	28 Stranded (7x36) .031" Insulated Conductor OD .186" Jacket OD	F/UTP No Spline	CMP	111S080800F3LA4	5mm (.197" Jacket OD) MUST USE B00067L BOOT for proper termination and strain relief	900005/900216

## DATAMAX CATEGORY 5e

## 24 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
1200 (BLACK), 1201 (BROWN), 1202 (RED), 1203 (ORANGE), 1204 (YELLOW), 1205 (GREEN), 1206 (BLUE), 1207 (VIOLET), 1208 (GRAY), 1209 (WHITE), 1210 (BEIGE), 1212 (PINK), 1215 (LIM)	24 Stranded (7x32) .039" Insulated Conductor OD .223" Jacket OD	U/UTP No Shield No Spline	CMX, LSZH	111-08080028L34	6mm (.240" Jacket OD)	900005/900216
5500 (BLACK), 5501 (BROWN), 5502 (RED), 5503 (ORANGE), 5504 (YELLOW), 5505 (GREEN), 5506 (BLUE), 5507 (VIOLET), 5508 (GRAY), 5509 (WHITE), 5510 (BEIGE), 5511 (LIGHT BLUE), 5512 (PINK), 5515 (LIME GREEN)	24 Stranded (7x32) .038" Insulated Conductor OD .215" Jacket OD	U/UTP No Shield No Spline	CMG, CMR	106-080800-34	6mm (.240" Jacket OD)	900005/900216

## 26 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2800 (BLACK), 2801 (BROWN), 2802 (RED), 2803 (ORANGE), 2804 (YELLOW), 2805 (GREEN), 2806 (BLUE), 2807 (VIOLET), 2808 (GRAY), 2809 (WHITE), 2810 (BEIGE)	26 Stranded (7x34) .039" Insulated Conductor OD .241" Jacket OD	F/UTP With Spline	CMX, LSZH	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
2900 (BLACK), 2901 (BROWN), 2902 (RED), 2903 (ORANGE), 2904 (YELLOW), 2905 (GREEN), 2906 (BLUE), 2907 (VIOLET), 2908 (GRAY), 2909 (WHITE), 2910 (BEIGE), 2912 (PINK)	26 Stranded (7x34) .039" Insulated Conductor OD .232" Jacket OD	F/UTP No Spline	CMR	111S08080028L34	6mm (.240" Jacket OD)	900005/900216

2510 (BLUE), 2511 (WHITE), 2512 (BEIGE), 2513 (LIGHT GRAY), 2514 (YELLOW)	26 Stranded (7x34) .036" Insulated Conductor OD .217" Jacket OD	F/UTP No Spline	CMR	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
---	---	--------------------	-----	-----------------	--------------------------	---------------

## Automation and Harsh Environment Data and Control Cables

### DataMax Extreme Industrial Ethernet/IP Hi Flex Category 6A/6

#### 4 Pair SF/UTP 26 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
5919 (BLACK)	26 Stranded (7x34) .036" Insulated Conductor OD .239" Jacket OD PUR	SF/UTP 4 Pair with Foil/Braid With Spline	EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
5026 (TEAL), 5047 (GRAY), 5048 (BLACK)	26 Stranded (7x34) .036" Insulated Conductor OD .275" Jacket OD TPE	SF/UTP 4 Pair with Foil/Braid With Spline	CM, CMX Outdoor EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080095HA4	8mm (.314" Jacket OD)	900020

#### 4 Pair SF/UTP 24 AWG STRANDED PATCH CABLES

5936	24 Stranded (7x32) .046" Insulated Conductor OD .291" Jacket OD TPE	SF/UTP 4 Pair with Foil/Braid With Spline	EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080090H34	8mm (.314" Jacket OD)	900020
------	--	--	---	-----------------	--------------------------	--------

**DataMax Extreme Industrial Ethernet/IP Hi Flex Category 5e**  
**4 Pair SF/UTP 26 AWG STRANDED PATCH CABLES**

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
5075 (BLACK), 5076 (BLUE), 5077 (TEAL), 5075 (RED), 5079 (YELLOW)	26 Stranded (7x34) .037" Insulated Conductor OD .246" Jacket OD PUR	SF/UTP 4 Pair with Foil/Braid No Spline	CMX, UL Oil Res.I EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
5083 (BLACK), 5084 (VIOLET), 5088 (TEAL), 5045 (BLUE), 5046 (RED)	26 Stranded (7x34) .037" Insulated Conductor OD .245" Jacket OD TPE	SF/UTP 4 Pair with Foil/Braid No Spline	CM, CMX Outdoor EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216

**2 Pair SF/UTP 26 AWG STRANDED PATCH CABLES**

5080 (BLACK), 5081 (BLUE), 5082 (TEAL)	26 Stranded (7x34) .037" Insulated Conductor OD .233" Jacket OD PUR	SF/UTP 2 Pair with Foil/Braid	CMX, UL Oil Res.I EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
---	--	-------------------------------------	---	-----------------	--------------------------	---------------



5055 (BLACK), 5056 (BLUE), 5057 (TEAL)	26 Stranded (7x34) .037" Insulated Conductor OD .225" Jacket OD PUR	SF/UTP 2 Pair with Foil/Braid	EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
5085 (BLACK), 5086 (BLUE), 5087 (TEAL)	26 Stranded (7x34) .037" Insulated Conductor OD .225" Jacket OD TPE	SF/UTP 2 Pair with Foil/Braid	CM, CMX Outdoor EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
<b>4 Pair U/UTP 24 AWG STRANDED PATCH CABLES</b>						
5700 (BLACK), 5703 (RED), 5706 (BLUE), 5716 (TEAL)	24 Stranded (7x32) .039" Insulated Conductor OD .245" Jacket OD PUR	U/UTP 4 Pair No Shield No Spline	x	111-08080028L34	6mm (.240" Jacket OD)	900005/900216
<b>2 Pair U/UTP 24 AWG STRANDED PATCH CABLES</b>						
5000 (BLACK), 5001 (RED), 5006 (BLUE), 5016 (TEAL)	24 Stranded (7x32) .039" Insulated Conductor OD .220" Jacket OD	U/UTP No Shield 2 Pair	x	111-08080028L34	6mm (.240" Jacket OD)	900005/900216
<b>4 Pair U/UTP 22 AWG STRANDED PATCH CABLES</b>						
5120 (BLACK), 5121 (BLUE), 5122 (TEAL)	24 Stranded (7x32) .047" Insulated Conductor OD .270" Jacket OD PUR	U/UTP 4 Pair No Shield No Spline	EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111-08080090L34	7mm (.275" Jacket OD)	900005/900216

**2 Pair U/UTP 22 AWG STRANDED PATCH CABLES**

5020 (BLACK), 5021 (BLUE), 5022 (TEAL)	22 Stranded (19/.0058) .047" Insulated Conductor OD .245" Jacket OD PUR	U/UTP No Shield 2 Pair	EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111-08080091L34	6.7mm (.264" Jacket OD)	900005/900216
--	--	------------------------------	---	-----------------	----------------------------	---------------

**DataMax Extreme Industrial Ethernet/IP Hi Flex AWM Style 2463 Category 6/6A**

**4 Pair SF/UTP 24 AWG STRANDED PATCH CABLES**

5922 (TEAL), 5925 (BLACK), 5935 (GRAY)	24 Stranded (7x32) .046" Insulated Conductor OD .325" Jacket OD TPE	SF/UTP 4 Pair with Foil/Braid With Spline	CM, CMX Outdoor EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080090H34	-	900020
--	--	--	--	-----------------	---	--------

**DataMax Extreme Industrial Ethernet/IP Hi Flex AWM Style 2463 Category 5e**

**4 Pair SF/UTP 24 AWG STRANDED PATCH CABLES**

5089 (BLACK), 5090 (TEAL), 5091 (BLUE), 5092 (RED), 5093 (VIOLET), 5097 (GRAY), 5934 (GREEN)	24 Stranded (7x32) .046" Insulated Conductor OD .290" Jacket OD TPE	SF/UTP 4 Pair with Foil/Braid No Spline	CM, CMX, UL AWM Style 2466 600V EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080090H34	8mm (.314" Jacket OD)	900020
--	--	--	--	-----------------	--------------------------	--------

**2 Pair SF/UTP 24 AWG STRANDED PATCH CABLES**

5023 (BLACK), 5024 (GRAY), 5025 (TEAL), 5027 (RED), 5028 (BLUE), 5029 (ORANGE)	24 Stranded (7x32) .047" Insulated Conductor OD .265" Jacket OD TPE	SF/UTP 2 Pair with Foil/Braid	CM, CMX, UL AWM Style 2463 600V EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111508080090C34	7mm (.275" Jacket OD)	900007
--	--	-------------------------------------	--	-----------------	--------------------------	--------

**4 Pair SF/UTP 22 AWG STRANDED PATCH CABLES**

5921(TEAL)	22 Stranded (19/.0058) .057" Insulated Conductor OD .354" Jacket OD TPE	SF/UTP 4 Pair with Foil/Braid No Spline	ITC, PLTC, UL AWM Style 2463 600V, UL Oil Res. I & II EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	No Cross Cable Too Large	-	-
------------	--	--	---	-----------------------------	---	---

**2 Pair SF/UTP 22 AWG STRANDED PATCH CABLES**

5920	22 Stranded (19/.0058) .054" Insulated Conductor OD .317" Jacket OD TPE	SF/UTP 2 Pair	CM, CMX Outdoor, ITC, PLTC, UL AWM Style 2463 600V, UL Oil Res. I & II EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	1145040800C34	8mm (.314" Jacket OD)	900007
------	--	------------------	---	---------------	--------------------------	--------

**4 Pair U/UTP 24 AWG STRANDED PATCH CABLES**

5750 (BLACK), 5751 (BLUE), 5752 (TEAL), 5753 (RED)	24 Stranded (7x32) .040" Insulated Conductor OD .248" Jacket OD TPE	U/UTP No Shield 2 Pair	CM, CMX Outdoor, UL AWM Style 2463 600V	111-08080028L34	6.7mm (.264" Jacket OD)	900005/900216
---	--	------------------------------	--	-----------------	----------------------------	---------------

**2 Pair U/UTP 24 AWG STRANDED PATCH CABLES**

5770 (BLACK), 5771 (BLUE), 5772 (TEAL), 5773 (RED)	24 Stranded (7x32) .039" Insulated Conductor OD .240" Jacket OD TPE	U/UTP No Shield 2 Pair	CM, CMX Outdoor, UL AWM Style 2463 600V	111-08080028L34	6mm (.240" Jacket OD)	900005/900216
---	--	------------------------------	---	-----------------	--------------------------	---------------

**4 Pair U/UTP 22 AWG STRANDED PATCH CABLES**

5800 (BLACK), 5801 (BLUE), 5802 (TEAL)	22 Stranded (19/.0058) .048" Insulated Conductor OD .270" Jacket OD TPE	U/UTP 4 Pair No Shield No Spline	CM, CMX Outdoor, MSHA, PLTC, UL AWM Style 2463 600V, UL Oil Res. I & II EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	1145040800C34	8mm (.314" Jacket OD)	900007
---	--	---	--	---------------	--------------------------	--------

**2 Pair U/UTP 22 AWG STRANDED PATCH CABLES**

5900 (BLACK), 5901 (BLUE), 5902 (TEAL)	22 Stranded (19/.0058) .048" Insulated Conductor OD .270" Jacket OD TPE	U/UTP No Shield 2 Pair	CM, CMX Outdoor, MSHA, PLTC, UL AWM Style 2463 600V, UL Oil Res. I & II EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	1145040800C34	8mm (.314" Jacket OD)	900007
---	--	------------------------------	--	---------------	--------------------------	--------

## DataMax Extreme Tough Horizontal AWM 2463 Category 5e

### 4 Pair U/UTP 22 AWG SOLID PATCH CABLES

5941 (BLACK), 5942 (TEAL)	22 Solid Bare Copper .045" Insulated Conductor OD .267" Jacket OD PVC	U/UTP 4 Pair No Shield No Spline	CMR, CMX Outdoor UL AWM 2463, PLTC, ITC EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111-08080090L34	7mm (.275" Jacket OD)	900005/900216
5943 (BLACK)	22 Solid Bare Copper .038" Insulated Conductor OD .230" Jacket OD PVC	U/UTP 4 Pair No Shield No Spline	CMR, CMX Outdoor UL AWM 2463, PLTC, ITC EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111-08080028L34	6mm (.240" Jacket OD)	900005/900216

## DataMax Extreme Industrial Ethernet Category 5e

### 4 Pair SF/UTP 26 AWG STRANDED PATCH CABLES

5730 (BLACK), 5731 (BLUE), 5732 (TEAL)	26 Stranded (7x34) .039" Insulated Conductor OD .220" Jacket OD PUR	SF/UTP 4 Pair with Foil/Braid No Spline	EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
5739 (BLACK), 5740 (BLUE), 5741 (TEAL)	26 Stranded (7x34) .039" Insulated Conductor OD .228" Jacket OD PVC	SF/UTP 4 Pair with Foil/Braid No Spline	CMR	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
5734 (BLACK), 5735 (BLUE), 5736 (TEAL)	26 Stranded (7x34) .039" Insulated Conductor OD .245" Jacket OD TPE	SF/UTP 4 Pair with Foil/Braid No Spline	CM, CMX Outdoor	111S08080028L34	6mm (.240" Jacket OD)	900005/900216

### 2 Pair SF/UTP 26 AWG STRANDED PATCH CABLES

5060 (BLACK), 5061 (BLUE), 5062 (TEAL)	26 Stranded (7x34) .039" Insulated Conductor OD .246" Jacket OD PVC	SF/UTP 2 Pair with Foil/Braid	CMR EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
---	--	-------------------------------------	--	-----------------	--------------------------	---------------

### 4 Pair F/UTP 26 AWG STRANDED PATCH CABLES

5710 (BLACK), 5711 (BLUE), 5712 (TEAL)	26 Stranded (7x34) .039" Insulated Conductor OD .227" Jacket OD PUR	F/UTP 4 Pair No Spline	EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
5725 (BLACK), 5726 (BLUE), 5727 (TEAL)	26 Stranded (7x34) .039" Insulated Conductor OD .225" Jacket OD PVC	F/UTP 4 Pair No Spline	CMR EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
5760 (BLACK), 5761 (BLUE), 5762 (TEAL), 5763 (RED)	26 Stranded (7x34) .039" Insulated Conductor OD .237" Jacket OD TPE	F/UTP 4 Pair with Foil No Spline	CMR	111S08080028L34	6mm (.240" Jacket OD)	900005/900216

**2 Pair F/UTP 26 AWG STRANDED PATCH CABLES**

5040 (BLACK), 5041 (BLUE), 5042 (TEAL)	26 Stranded (7x34) .039" Insulated Conductor OD .229" Jacket OD PUR	F/UTP 2 Pair	EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
5035 (BLACK), 5036 (BLUE), 5037 (TEAL), 5038 (RED)	26 Stranded (7x34) .040" Insulated Conductor OD .209" Jacket OD TPE	F/UTP 2 Pair	CM EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216

5030 (BLACK), 5031 (BLUE), 5032 (TEAL)	26 Stranded (7x34) .040" Insulated Conductor OD .209" Jacket OD PVC	F/UTP 2 Pair	CMR EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
<b>4 Pair F/UTP 24 AWG STRANDED PATCH CABLES</b>						
5928 (BLACK), 5929 (TEAL)	24 Stranded (7x32) .047" Insulated Conductor OD .273" Jacket OD TPE	F/UTP 4 Pair No Spline	CM, CMX Outdoor EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080090C34	7mm (.275" Jacket OD)	900007
<b>4 Pair U/UTP 24 AWG STRANDED PATCH CABLES</b>						
5915 (BLACK), 5916 (TEAL), 5917 (BLUE), 5918 (RED)	24 Stranded (7x32) .227" Jacket OD PVC	U/UTP 4 Pair No Shield No Spline	CMR	111-08080028L34	6mm (.240" Jacket OD)	900005/900216
<b>2 Pair U/UTP 24 AWG STRANDED PATCH CABLES</b>						
5780 (BLACK), 5781 (BLUE), 5782 (TEAL), 5783 (RED)	24 Stranded (7x32) .039" Insulated Conductor OD .220" Jacket OD PVC	U/UTP 2 Pair No Shield No Spline	CMR	111-08080028L34	6mm (.240" Jacket OD)	900005/900216

**DataMax Extreme Profinet Hi Flex Category 6/6A**



**2 PR/ 4C      SF/UTP      22 AWG STRANDED PATCH CABLES**

5098 (GREEN)	22 Stranded (19/.0058) .055" Insulated Conductor OD .410" Jacket OD TPE	SF/UTP 2 Pair with Foil/Braid	PLTC-ER, CM	No Cross Cable Too Large	-	-
5099 (GREEN)	22 Stranded (7/32) .050" Insulated Conductor OD .305" Jacket OD TPE	SF/UTP 4 Conductor with Foil/Braid	CM, PLTC, PLTC-ER EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080091H34	8mm (.314" Jacket OD)	900020

**DataMax Extreme Profinet Hi Flex AWM Style 2463 Category 6/6A**

**4 Pair      SF/UTP      24 AWG STRANDED PATCH CABLES**

5937 (LIME GREEN)	24 Stranded (7x32) .046" Insulated Conductor OD .325" Jacket OD TPE	SF/UTP 4 Pair with Foil/Braid With Spline	UL AWM 2463 CM, CMX Outdoor EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	111S08080090H34	-	900020
-------------------	--	--	---	-----------------	---	--------

**DataMax Extreme Profinet Hi Flex AWM Style 2463 Category 5e**

**2 PR/4C      SF/UTP      22 AWG STRANDED PATCH CABLES**

5924 (GREEN)	22 Stranded (19/.0058) .054" Insulated Conductor OD .317" Jacket OD TPE	SF/UTP 2 Pair with Foil/Braid	UL AWM 2463, PLTC, ITC, PA DEP - MSHA EU CE MARK: Meets EU Directive 2011/65/EU (RoHS II)	106S080800D6H34	8mm (.314" Jacket OD)	900021
5094 (GREEN)	22 Stranded (7/30) .066" Insulated Conductor OD .260" Jacket OD	SF/UTP 4 Conductor with Foil/Braid	x	No Cross Cable Too Large	-	-