



## DATAMAX CATEGORY 6A - F/UTP - 26 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2942 (BLACK), 2943 (BROWN), 2944 (RED), 2945 (ORANGE), 2946 (YELLOW), 2947 (GREEN), 2948 (BLUE), 2949 (VIOLET), 2950 (GRAY), 2951 (WHITE), 2952 (BEIGE), 2953 (PINK), 2991 (AQUA)	26 Stranded (7x34) .036" Insulated Conductor OD .235" Jacket OD	F/UTP With Spline	CMG, CMR	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
2978 (BLACK), 2979 (BROWN), 2980 (RED), 2981 (ORANGE), 2982 (YELLOW), 2983 (GREEN), 2984 (BLUE), 2985 (VIOLET), 2986 (GRAY), 2987 (WHITE), 2988 (BEIGE), 2989 (PINK)	26 Stranded (7x34) .036" Insulated Conductor OD .265" Jacket OD	F/UTP With Spline	CMX, LSZH	111S08080095HA4	7mm (.275" Jacket OD)	900020
2056 (BLACK), 2057 (BROWN), 2058 (RED), 2059 (ORANGE), 2060 (YELLOW), 2061 (GREEN), 2062 (BLUE), 2063 (VIOLET), 2064 (GRAY), 2065 (WHITE), 2066 (BEIGE)	26 Stranded (7x34) .039" Insulated Conductor OD .223" Jacket OD	F/UTP No Spline	CMP	111S080800C7LA4	6mm (.240" Jacket OD)	900005/900216
2279 (BLACK), 2280 (RED), 2281 (ORANGE), 2282 (YELLOW), 2283 (GREEN), 2284 (BLUE), 2285 (VIOLET), 2286 (GRAY), 2287 (WHITE)	26 Stranded (7x34) .0405" Insulated Conductor OD .235" Jacket OD	Relaxed F/UTP No Spline	CM-ST1, CM, LSZH	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
2246 (BLACK), 2247 (BROWN), 2248 (RED), 2249 (ORANGE), 2250 (YELLOW), 2251 (GREEN), 2252 (BLUE), 2253 (VIOLET), 2254 (GRAY), 2255 (WHITE), 2256 (BEIGE), 2257 (PINK), 2258 (AQUA), 2259 (LT Blue)	26 Stranded (7x34) .0405" Insulated Conductor OD .233" Jacket OD	Relaxed F/UTP No Spline	CMG, CMR, EU CE MARK	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216



## DATAMAX CATEGORY 6A - F/UTP - 28 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2231 (BLACK), 2232 (BROWN), 2233 (RED), 2234 (ORANGE), 2235 (YELLOW), 2236 (GREEN), 2237 (BLUE), 2238 (VIOLET), 2239 (GRAY), 2240 (WHITE), 2241 (BEIGE), 2242 (LIGHT BLUE), 2243 (PINK), 2244 (AQUA), 2245 (LIME GREEN)	28 Stranded (7x36) .0325" mim .0331" max Insulated Conductor OD .186" Jacket OD	F/UTP No Spline	CMR	111S080800F3LA4	5mm (.197" Jacket OD) MUST USE B00067L BOOT for proper termination and strain relief	900005/900216
2270 (BLACK), 2271 (RED), 2272 (ORANGE), 2273 (YELLOW), 2274 (GREEN), 2275 (BLUE), 2276 (VIOLET), 2277 (GRAY), 2278 (WHITE)	28 Stranded (7x36) .0325" mim .0331" max Insulated Conductor OD .190" Jacket OD	F/UTP No Spline	CM-ST1, CM, LSZH	111S080800F3LA4	5mm (.197" Jacket OD) MUST USE B00067L BOOT for proper termination and strain relief	900005/900216
2034 (BLACK), 2035 (BROWN), 2036 (RED), 2037 (ORANGE), 2038 (YELLOW), 2039 (GREEN), 2040 (BLUE), 2041 (VIOLET), 2042 (GRAY), 2043 (WHITE), 2044 (STARLIGHT BEIGE)	28 Stranded (7x36) .031" Insulated Conductor OD .186" Jacket OD	F/UTP No Spline	CMP	111S080800F3LA4	5mm (.197" Jacket OD) MUST USE B00067L BOOT for proper termination and strain relief	900005/900216



## DATAMAX CATEGORY 6 - U/UTP - 24 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2200 (BLACK), 2201 (BROWN), 2202 (RED), 2203 (ORANGE), 2204 (YELLOW), 2205 (GREEN), 2206 (BLUE), 2207 (VIOLET), 2208 (GRAY), 2209 (WHITE), 2210 (BEIGE), 2211 (LIGHT BLUE), 2212 (PINK), 2213 (AQUA), 2215 (LIME)	24 Stranded (7x32) .039" Insulated Conductor OD .220" Jacket OD	U/UTP No Shield No Spline	CMR	111-08080054L34	6mm (.240" Jacket OD)	900005/900216
2200B (BLACK), 2201B (BROWN), 2202B (RED), 2203B (ORANGE), 2204B (YELLOW), 2205B (GREEN), 2206B (BLUE), 2207B (VIOLET), 2208B (GRAY), 2209B (WHITE), 2210B (BEIGE), 2212B (PINK), 2215B (LIME)	24 Stranded (7x32) .039" Insulated Conductor OD .220" Jacket OD	U/UTP No Shield No Spline	CMG, CMR	111-08080054L34	6mm (.240" Jacket OD)	900005/900216
1300 (BLACK), 1301 (BROWN), 1302 (RED), 1303 (ORANGE), 1304 (YELLOW), 1305 (GREEN), 1306 (BLUE), 1307 (VIOLET), 1308 (GRAY), 1309 (WHITE), 1310 (BEIGE), 1312 (PINK)	24 Stranded (7x32) .039" Insulated Conductor OD .231" Jacket OD	U/UTP No Shield No Spline	CMX, LSZH	111-08080054L34	6mm (.240" Jacket OD)	900005/900216
2016 (BLACK), 2017 (RED), 2018 (ORANGE), 2019 (YELLOW), 2020 (GREEN), 2012 (BLUE), 2022 (VIOLET), 2023 (GRAY), 2024 (WHITE)	24 Stranded (7x32) .039" Insulated Conductor OD .227" Jacket OD	U/UTP No Shield No Spline	CM-ST1, CM, LSZH	111-08080054L34	6mm (.240" Jacket OD)	900005/900216

## DATAMAX CATEGORY 6 - F/UTP - 26 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2966 (BLACK), 2967 (BROWN), 2968 (RED), 2969 (ORANGE), 2970 (YELLOW), 2971 (GREEN), 2972 (BLUE), 2973 (VIOLET), 2974 (GRAY), 2975 (WHITE), 2976 (BEIGE), 2977 (PINK)	26 Stranded (7x34) .036" Insulated Conductor OD .265" Jacket OD	F/UTP With Spline	CMX, LSZH	111S08080095LA4	7mm (.275" Jacket OD)	900005/900216
2930 (BLACK), 2931 (BROWN), 2932 (RED), 2933 (ORANGE), 2934 (YELLOW), 2935 (GREEN), 2936 (BLUE), 2937 (VIOLET), 2938 (GRAY), 2939 (WHITE), 2940 (BEIGE), 2941 (PINK)	26 Stranded (7x34) .036" Insulated Conductor OD .235" Jacket OD	F/UTP With Spline	CM, CMG, CMR	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
2025 (BLACK), 2026 (RED), 2027 (ORANGE), 2028 (YELLOW), 2029 (GREEN), 2030 (BLUE), 2031 (VIOLET), 2032 (GRAY), 2033 (WHITE)	26 Stranded (7x34) .036" Insulated Conductor OD .235" Jacket OD	F/UTP No Spline	CM-ST1, CM, LSZH	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
2157 (BLACK), 2158 (BROWN), 2159 (RED), 2160 (ORANGE), 2161 (YELLOW), 2162 (GREEN), 2163 (BLUE), 2164 (VIOLET), 2165 (GRAY), 2166 (WHITE), 2167 (BEIGE), 2168 (PINK)	26 Stranded (7x34) .0405" Insulated Conductor OD .233" Jacket OD	Relaxed F/UTP No Spline	CMG, CMR, EU CE MARK	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216
2067 (BLACK), 2068 (BROWN), 2069 (RED), 2070 (ORANGE), 2071 (YELLOW), 2072 (GREEN), 2073 (BLUE), 2074 (VIOLET), 2075 (GRAY), 2076 (WHITE), 2077 (BEIGE)	26 Stranded (7x34) .039" Insulated Conductor OD .223" Jacket OD	F/UTP No Spline	CMP	111S08080095LA4	6mm (.240" Jacket OD)	900005/900216



## DATAMAX CATEGORY 6 - U/UTP & F/UTP - 28 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2260 (BLACK), 2261 (RED), 2262 (ORANGE), 2263 (YELLOW), 2264 (GREEN), 2265 (BLUE), 2266 (VIOLET), 2267 (GRAY), 2268 (WHITE), 2269 (PINK)	28 Stranded (7x36) .0245" Insulated Conductor OD .150" Jacket OD	U/UTP No Shield No Spline	CM-ST1, CM, LSZH	111-080800B5LA4	4.06mm (.160" Jacket OD) MUST USE B00058L BOOT for proper termination and strain relief	900005/900216
2216 (BLACK), 2217 (BROWN), 2218 (RED), 2219 (ORANGE), 2220 (YELLOW), 2221 (GREEN), 2222 (BLUE), 2223 (VIOLET), 2224 (GRAY), 2225 (WHITE), 2226 (BEIGE), 2227 (LIGHT BLUE), 2228 (PINK), 2229 (AQUA), 2230 (LIME)	28 Stranded (7x36) .0245" Insulated Conductor OD .150" Jacket OD	U/UTP No Shield No Spline	CMR	111-080800B5LA4	4.06mm (.160" Jacket OD) MUST USE B00058L BOOT for proper termination and strain relief	900005/900216
2045 (BLACK), 2046 (BROWN), 2047 (RED), 2048 (ORANGE), 2049 (YELLOW), 2050 (GREEN), 2051 (BLUE), 2052 (VIOLET), 2053 (GRAY), 2054 (WHITE), 2055 (STARLIGHT BEIGE)	28 Stranded (7x36) .031" Insulated Conductor OD .186" Jacket OD	U/UTP No Shield No Spline	CMP	111S080800F3LA4	5mm (.197" Jacket OD) MUST USE B00067L BOOT for proper termination and strain relief	900005/900216



## DATAMAX CATEGORY 5e - U/UTP - 24 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
1200 (BLACK), 1201 (BROWN), 1202 (RED), 1203 (ORANGE), 1204 (YELLOW), 1205 (GREEN), 1206 (BLUE), 1207 (VIOLET), 1208 (GRAY), 1209 (WHITE), 1210 (BEIGE), 1212 (PINK), 1215 (LIME)	24 Stranded (7x32) .039" Insulated Conductor OD .223" Jacket OD	U/UTP No Shield No Spline	CMX, LSZH	111-08080028L34	6mm (.240" Jacket OD)	900005/900216
5500 (BLACK), 5501 (BROWN), 5502 (RED), 5503 (ORANGE), 5504 (YELLOW), 5505 (GREEN), 5506 (BLUE), 5507 (VIOLET), 5508 (GRAY), 5509 (WHITE), 5510 (BEIGE), 5511 (LIGHT BLUE), 5512 (PINK), 5515 (LIME GREEN)	24 Stranded (7x32) .038" Insulated Conductor OD .215" Jacket OD	U/UTP No Shield No Spline	CMG, CMR	106-080800-34	6mm (.240" Jacket OD)	900005/900216

## DATAMAX CATEGORY 5e - F/UTP - 26 AWG STRANDED PATCH CABLES

Quabbin Part Numbers	AWG	Shielding	Rating	Sentinel Plug	Boot	Termination Tool
2800 (BLACK), 2801 (BROWN), 2802 (RED), 2803 (ORANGE), 2804 (YELLOW), 2805 (GREEN), 2806 (BLUE), 2807 (VIOLET), 2808 (GRAY), 2809 (WHITE), 2810 (BEIGE)	26 Stranded (7x34) .039" Insulated Conductor OD .241" Jacket OD	F/UTP With Spline	CMX, LSZH	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
2900 (BLACK), 2901 (BROWN), 2902 (RED), 2903 (ORANGE), 2904 (YELLOW), 2905 (GREEN), 2906 (BLUE), 2907 (VIOLET), 2908 (GRAY), 2909 (WHITE), 2910 (BEIGE), 2912 (PINK)	26 Stranded (7x34) .039" Insulated Conductor OD .232" Jacket OD	F/UTP No Spline	CMR	111S08080028L34	6mm (.240" Jacket OD)	900005/900216
2510 (BLUE), 2511 (WHITE), 2512 (BEIGE), 2513 (LIGHT GRAY), 2514 (YELLOW)	26 Stranded (7x34) .036" Insulated Conductor OD .217" Jacket OD	F/UTP No Spline	CMR	111S08080028L34	6mm (.240" Jacket OD)	900005/900216